

Ultra Low Nox Light Duty Commercial Gas Water Heater Atmospheric Vent

American Standard[®]

WATER HEATERS

www.americanstandardwaterheaters.com

Model Available in 75 & 100 Gallon Capacities

76,000 BTU in Natural and LP Gas

These American Standard Commercial Gas Models are designed to fulfill the hot water requirements of large residential, business and multi-family developments up to four double baths units (PLC 75-76) or up to seven single or five double baths units (PLC 100-76).

Features

- **HEAVY GAUGE STEEL TANK** – For extra years of trouble-free service.
- **INNER TANK GLASS-LINED** – With Dura-Glas™ and fired at 1600° F for optimum protection from the effects of corrosion.
- **R-16 NON-CFC FOAM INSULATED** – To save energy and reduce fuel costs by maximizing heat retention.
- **TWO ANODE ROD** – To extend tank life.
- **SELF-CLEANING TURBULENCE INDUCING COLD WATER INLET-TUBE** – Engineered to diminish hard water area sediment deposits.
- **FULL SIZE HAND-HOLE CLEANOUT** – For convenient tank inspection and removal of sediment deposits.
- **FURNISHED WITH HEAVY GAUGE STEEL LEGS** – Designed to maximize durability & provide stability during installation.
- **AUTOMATIC GAS THERMOSTAT ADJUSTABLE TO 180° F** – When installed with a mixing valve, can deliver 180° F and 140° F general purpose hot water simultaneously.
- **COMBUSTION CHAMBER DOOR** – Including hinged knob outside access & sliding inner door to isolate burner & pilot area for additional safety.
- **FACTORY INSTALLED ENERGY CUT-OFF SYSTEM AND TEMPERATURE & PRESSURE RELIEF VALVE.**
- **SMALL VENT SIZE & TOP MOUNT WATER CONNECTIONS** – Allow for universal replacement of other brands (PLC 75-76 AS = 1" & PLC 100-76 AS = 1 1/4").
- **AMERICAN STANDARD GAS WATER HEATERS** – Are certified at 300 PSI test pressure & for 150 PSI working pressure.
- **ALL TANKS ARE HYDROSTATICALLY TESTED AT THE FACTORY.**
- **TESTED & LISTED WITH ETL INTERTEK** – In accordance with ANSI, Z.21.10.3, up to 180° F operation as an automatic storage and/or automatic circulating tank heater. ASHRAE Standard 90.1 1999 addendum 90.1b. ETL Certified to meet NSF/ANSI 5 Standards.
- **FOUR YEAR LIMITED TANK WARRANTY** – On inner glass lined tank and one year limited warranty on all other components.



Intertek

